

WASH AND RINSE SYSTEM FOR A DISHWASHER

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application constitutes a continuation-in-part of U.S. Patent Application Serial Number 10/186,739 entitled “DISHWASHER
5 PUMP AND FILTRATION SYSTEM” filed July 2, 2002, pending, and a continuation-in-part of U.S. Patent Application Serial Number 10/186,714 entitled “METHOD OF OPERATING A DISHWASHER PUMP AND FILTRATION SYSTEM” filed on July 2, 2002, pending.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

The present invention pertains to the art of dishwashers and, more particularly, to a wash and rinse system employed in a dishwasher.

2. Discussion of the Prior Art

Automatic dishwashers are typically provided with a control system that performs various cycles of an overall wash operation. Generally, the various cycles include wash, rinse and dry operations.

5 Prior to each wash and rinse cycle, an amount of water is admitted into a washing chamber of the dishwasher to establish a washing fluid. The washing fluid is pumped to a spray arm that directs jets of the fluid onto kitchenware being washed in the washing chamber. The jets of washing

10 fluid impinge upon the kitchenware to dislodge food and soil particles. Typically, the food and soil particles fall into a bottom or sump portion of the washing chamber where they are filtered out of the washing fluid. However, often times, the jets of washing fluid will cause the food and soil particles to fly off the kitchenware and adhere to internal surfaces of the washing chamber.

15 Typically, the food and soil particles that fly off under force of the jets are later washed off the internal surfaces of the washing chamber by the jets themselves. However, the jets of washing fluid simply do not impinge upon all regions of the washing chamber during the wash and rinse cycles. For this reason, food and soil particles can begin to

20 accumulate in the regions that are not normally washed by the jets.

Typically, these regions exist at lower corners of the tub or at the front of the tub, where a lower portion of the dishwasher door actually operates to shield the spray jets from effectively cleaning this area. If left unchecked, food and soil particles can accumulate over time to a degree that would

25 negatively impact the ability of the dishwasher to properly cleanse the kitchenware, as well as consumer appeal. In addition, the food and soil particles left on the internal surfaces of the washing chamber could

ultimately result in stains that would be difficult, if not impossible, to fully remove.

Based on the above, there exists a need for a dishwasher that includes a system for dislodging food and soil particles that adhere to internal surfaces of the washing chamber. More specifically, there exists
5 a need for a system that will remove food and soil particles from lower regions of the washing chamber and, particularly, from front regions of the washing chamber adjacent to a bottom portion of the door.

SUMMARY OF THE INVENTION

10 The present invention is directed to a wash and rinse system for a dishwasher. More specifically, the present invention is directed to a wash and rinse system that dislodges food and soil particles adhering to lower portions of a washing chamber of the dishwasher. In accordance with a preferred embodiment of the present invention, the washing chamber is
15 filled with a washing fluid to a first level. Preferably, the first level reaches a bottom portion of a door provided to selectively seal the washing chamber.

During a wash or rinse cycle, a majority of the washing fluid is drawn into a wash system which includes at least a circulation pump and
20 at least one wash or spray arm for directing jets of washing fluid onto kitchenware placed in the dishwasher. At the start of a wash or rinse cycle, the wash pump is activated such that the washing fluid is drawn into the wash system, while the washing fluid remaining in the washing

chamber falls to a second level. Activation of the pump also initiates jets of washing fluid that impinge upon the kitchenware. The jets of washing fluid cause food and soil particles on the kitchenware to become dislodged, at which point they are either led into a filter system or adhere to internal surfaces of the washing chamber. In order to dislodge the soil particles from the internal surfaces of the washing chamber, so that proper filtration and drainage can occur, the washing fluid in the washing chamber is returned to the first level. As the level of the washing fluid rises, food and other soil particles are dislodged from corner and other lower surfaces of the washing chamber.

In further accordance with the preferred embodiment of the present invention, the washing fluid is returned to the first level by pausing the wash pump. That is, each wash and/or rinse cycle preferably incorporates at least one pause period during which time the wash pump is deactivated. Preferably, a pause period is established during both a main wash cycle and a final rinse cycle. During each pause period, washing fluid suspended in the wash system re-enters the washing chamber causing the washing fluid to rise back to the first level. More preferably, each wash and/or rinse cycle includes a plurality of pause periods to substantially prevent food or soil particles from undesirably adhering to lower internal surfaces of the washing chamber.

In still further accordance with the preferred embodiment of the present invention, after each pause period, the washing fluid is delivered to the at least one wash arm in a manner to establish a variable spray pattern in the washing chamber. In accordance with this aspect of the invention, the wash pump is controlled such that the pressure of the

washing fluid is gradually increased in order to purposefully vary a trajectory of the jets of washing fluid. In this manner, the jets of washing fluid will be caused to impinge upon regions of the washing chamber typically left untouched by the jets of washing fluid. That is, as the pressure increases, the trajectory of the jets will continually direct washing fluid to portions of the washing chamber that, under full pressure conditions, are typically not directly impacted by the jets of washing fluid, thereby further removing soil adhering to these tub portions.

Additional objects, features and advantages of the present invention will become more readily apparent from the following detailed description of a preferred embodiment when taken in conjunction with the drawings wherein like reference numerals refer to corresponding parts in the several views.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an upper right perspective view of a dishwasher constructed in accordance with the present invention, with a door of the dishwasher being open;

Figure 2 is another perspective view of the dishwasher of Figure 1 with the door open;

Figure 3 is a perspective view of an overall pump and filtration system incorporated in the dishwasher of the invention;

Figure 4 is an isometric, cross-sectional view through both a tub basin and the overall pump and filtration system of the dishwasher of Figure 1;

Figure 5 is a perspective, cross-sectional view through the tub basin and the pump/filtration system;

Figure 6 is an elevational, cross-sectional view through the tub basin and the pump/filtration system;

Figure 7 is another elevational, cross-sectional view through the tub basin and the pump/filtration system;

Figure 8 is a perspective view of a flapper valve incorporated in the pump and filtration system of the invention;

Figure 9 is an enlarged, perspective view of the recirculation pump, along with the lower wash arm, shown in the overall system of Figure 3;

Figure 10 is an upper perspective view of a filter guard shown mounted atop the recirculation pump in Figure 9;

Figure 11 is a lower perspective view of the filter guard of Figure 9;

Figure 12 is a perspective view of a modified water conduit and overflow tube arrangement for the dishwasher of Figure 1; and

Figure 13 is a block diagram of a control unit for the dishwasher.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With initial reference to Figures 1-3, a dishwasher constructed in accordance with the present invention as generally indicated at 2. As shown, dishwasher 2 includes a tub 5 which is preferably injection molded of plastic or formed of stainless steel so as to include integral bottom, side, rear and top walls 8-12 respectively. Within the confines of walls 8-12, tub 5 defines a washing chamber 14 within which soiled kitchenware is adapted to be placed upon shiftable upper and lower racks (not shown), with the kitchenware being cleaned during a washing operation in a manner widely known in the art. Tub 5 has attached thereto a frontal frame 16 which pivotally supports a door 20 used to seal chamber 14 during a washing operation. As shown, door 20 is pivotally supported to frame 16 at a bottom portion 21. In connection with the washing operation, door 20 is preferably provided with a detergent tray assembly 23 within which a consumer can place liquid or particulate washing detergent for dispensing at predetermined portions of the washing operation. Door 20 is also provided with a liner 24 within which is arranged detergent tray assembly 23. Liner 24 also includes a lower lip portion 25 that extends across bottom portion 21 of door 20. Of course, dispensing detergent in this fashion is known in the art such that this arrangement is only being described for the sake of completeness.

Disposed within tub 5 and, more specifically, mounted within a central opening 27 (see Figures 4-7) molded or formed in bottom wall 8 of tub 5, is a pump assembly 30. In the preferred embodiment and as illustrated in these figures, pump assembly 30 includes a main housing 33, an annular, radial outermost strainer 36 and a filter guard 39. A detailed description of the exact structure and operation of pump assembly 30 will be described more fully below. Extending about a substantial portion of pump assembly 30, at a position raised above bottom wall 8, is a heating element 44. In a manner known in the art, heating element 44 preferably takes the form of a sheath, electric resistance-type heating element.

In general, pump assembly 30 is adapted to direct washing fluid to at least a lower wash arm 47 and a conduit 51. As depicted, conduit 51 includes a substantially horizontal, lower section 53 extending away from main housing 33 of pump assembly 30, a vertical section 54 which generally extends along rear wall 11, and a generally horizontally extending upper section 55 which rotatably supports an upper wash arm 59. Vertical section 54 has attached thereto a wash fluid diverter 66 which defines upper and lower ports 68 and 69. Although not considered part of the present invention, each of upper and lower ports 68 and 69 has associated therewith a valve, such as a flapper element indicated at 72, for preventing any water flowing through conduit 51 from exiting either of port 68 or 69 unless structure is inserted into a respective port 68, 69 so as to deflect a respective flapper element 72. In general, wash fluid diverter 66 can actually be formed with a varying number of ports ranging from 1 to 3 or more. The overall wash fluid diverter 66 is actually designed to cooperate with a vertically adjustable upper rack (not shown) which

would carry an associated underside wash arm and respective piping that would become aligned with and project into a respective port 68, 69 in order to deflect flapper element 72 so as to provide an additional wash arm used to further spray washing fluid upon kitchenware, thereby
5 supplementing lower wash arm 47 and upper wash arm 59 during a washing operation within dishwasher 2. In general, vertically adjustable racks, as well as multi-port wash fluid diverters are known in the art such that this structure will not be described further here.

Pump assembly 30 has associated therewith a drain port 76 to
10 which is attached a drain pump 79. Drain pump 79 is secured beneath bottom wall 8 of tub 5 through the use of a suspension bracket 82. Drain pump 79 has associated therewith a drain hose 85 including at least one corrugated or otherwise curved portion 89 that extends about an arcuate hanger 92 provided on an outside surface of side wall 10. Drain hose 85
15 is also preferably secured to tub 5 through various clips, such as that indicated at 95. In any event, in this manner, an upper loop is maintained in drain hose 85 to assure proper drainage in a manner known in the art.

Also projecting from main housing 33 of pump assembly 30 is an overflow tube 98. More specifically, overflow tube 98 includes a first
20 end 99 leading from main housing 33 in a manner which will be detailed more fully below, as well as a second end 100 which leads into an overflow housing 104. In accordance with the preferred embodiment shown in these drawings, overflow tube 98 is preferably integrated into conduit 51 during manufacturing, such as through a blow molding or
25 extrusion operation. In any event, second end 100 of overflow tube 98 leads out of the overall structure defining conduit 51 to direct fluid from

within overflow tube 98 into overflow housing 104. Overflow housing 104 incorporates a coarse filter 106. In one preferred embodiment, filter 106 has openings in the order of 20 mils. Although a removable cover could be provided to access filter 106 for replacement/cleaning purposes, 5 filter 106 is preferably molded into housing 104 such that the entire housing/filter unit would be replaced if necessary. However, as will be detailed further below, a backwashing arrangement for filter 106 is preferably employed for cleansing purposes. In any event, further details on the construction and operation of this overflow arrangement will be 10 provided below in describing the overall operation of pump assembly 30.

At this point, reference will now be made to Figures 4-7 in describing further details of pump assembly 30, as well as other components of dishwasher 2. As best shown in Figure 4, side walls 9 and 10 lead into bottom wall 8 through a pair of spaced plateau portions 121 15 and 122. Rollers for a lower rack (not shown) are adapted to be supported upon plateau portions 121 and 122 for movement of the rack into and out of tub 5. In any event, bottom wall 8 includes a lower base portion 126 which slopes inwardly towards a trough 129. Trough 129 defines an inlet trap which is generally U-shaped in cross-section as 20 clearly shown in each of Figures 4-7. Radially inwardly of trough 129, bottom wall 8 includes an inner radial plateau portion 132 that leads to a downwardly extending portion 135 and finally a substantially horizontally extending innermost portion 137. Innermost portion 137 defines central opening 27 within which pump assembly 30 extends as 25 clearly shown in these figures.

Pump assembly 30 includes a lower housing plate 145 that includes a central recess section 148 and an outer edge 152. Spaced slightly inwardly from outer edge 152, lower housing plate 145 is provided with a lower rib 155. As shown, lower rib 155 extends into a notch (not labeled) defined in a seal 160. More specifically, seal 160 is sandwiched between downwardly extending portion 135 and lower rib 155, while also projecting along outer edge 152. In this manner, fluid that flows through trough 129 and along inner-radial plateau portion 132 is prevented from reaching innermost portion 137, but rather is forced to flow above lower housing plate 145.

Pump assembly 30 has associated therewith a motor 165. In general, motor 165 is of the type known in the art and includes a housing 168 and an associated driveshaft 170 which is rotatably supported by housing 168 through upper and lower bearing units 172 and 173. Since the general construction and operation of motor 165 is known in the art, it will not be detailed further herein. However, it should be noted that driveshaft 170 is secured for concurrent rotation with a lower drive sleeve 174, which is spaced from an upper sleeve 175. Although not shown in detail, lower drive sleeve 174 is preferably formed of two parts which securely sandwiches a chopper blade 178 therebetween. In this manner, chopper blade 178, which extends substantially parallel to but spaced vertically above lower housing plate 145, rotates in unison with driveshaft 170 during operation of motor 165. Arranged above chopper blade 178 is a fixed, apertured plate 182. As clearly shown in at least Figures 4 and 5, plate 182 actually includes a plurality of spaced holes 184 which are sized to permit passage of only predetermined sized

particles entrained within washing fluid as will be detailed more fully below.

At this point, it should be noted that apertured plate 182 is actually secured to an annular rib 186 which projects downward from an intermediate housing plate 189. Actually, intermediate housing plate 189 has arranged radially outward of annular rib 186 a plurality of annularly spaced bosses, one of which is indicated at 193 in Figure 7, for securing fixed apertured plate 182 in a desired position. Intermediate housing plate 189 also includes a series of upstanding, radially spaced ribs 195-197 which project in a direction opposite to annular rib 186, as well as an additional rib 198 which extends downward from intermediate housing plate 189. For reasons which will be discussed more fully below, rib 198 actually defines a flow plate which projects into trough 129. Ribs 196 and 197 extend upwardly substantially parallel to one another and define a filter chamber 202. A cover 204, which includes a plurality of enlarged openings 206, spans across ribs 196 and 197. As best illustrated in Figures 4 and 5, each of enlarged openings 206 has associated therewith a fine mesh screen 207, preferably having openings in the order of 75 microns or 3 mils, for filtering purposes. Filter chamber 202 is open, at one side of pump assembly 30, to a collection chamber 212. This arrangement is best shown in Figures 4 and 5, with these figures also indicating the manner in which cover 204 is secured to intermediate housing plate 189 as well as bottom wall 8.

More specifically, cover 204 is provided with various annularly spaced holes, one of which is indicated at 214 aligned with a respective upstanding sleeve 215 projecting up from intermediate housing plate 189,

as well as a respective mounting boss 216 formed integral with bottom wall 8 or integral with lower housing plate 145 (stainless steel tub models). Upon aligning these components in this manner, mechanical fasteners (not shown) are placed through a respective hole 214 and sleeve 215 and secured within respective bosses 216. In any event, at this point, it is merely important to note that filter chamber 202 extends about a top portion of pump assembly 30 and is in fluid communication with collection chamber 212 which, as will be discussed more fully below, is in fluid communication with drain port 76 and drain pump 79.

With further reference to each of Figures 4-6, intermediate housing plate 189 locates a pump component indicated at 218. Rotating with pump component 218 is another pump component or impeller 220. As shown, impeller 220 is also spaced from upper sleeve 175. In any event, impeller 220 is drivingly connected to driveshaft 170 so as to rotate in unison with driveshaft 170 and chopper blade 178 during operation of motor 165. Although further details will be provided below, at this point, it should be noted that components 218 and 220 collectively define a recirculating pump incorporated in the overall pump assembly 30.

In accordance with the most preferred embodiment, arranged above impeller 220 is a fixed involute manifold 226. Involute manifold 226 is shown to include a first involute member 228 and a second involute member 232 which are intermeshed in a manner defining a radially spiraling chamber. Second involute member 232 is preferably formed as part of a pump housing cap 235 having an outermost radial portion 239 provided with at least one annular recess 242 into which projects rib 195 of intermediate housing plate 189. A second annular recess 243 is

defined radially outwardly of annular recess 242 as clearly shown in these figures. In any event, it is merely important to note that pump housing cap 235 is fixed to intermediate housing plate 189 with at least the positioning of rib 195 in annular recess 242 creating a seal between these members. In the embodiment shown, pump housing cap 235 actually includes an outermost radial portion, i.e., a lower region 239 that defines annular recesses 242 and 243, an intermediate region 248 defining second involute member 232, and an upper region 250 provided with a central opening 253. A shaft 257 which is secured to first involute member 228 extends through both opening 253 and a sleeve 260 formed integral with lower wash arm 47 in order to rotatably support lower wash arm 47. As also illustrated in these figures, upper region 250 also opens into lower section 53 of conduit 51. As best shown in Figure 7, prior to vertical section 54, conduit 51 is formed with a sampling port 267 which opens into a cylinder member 268 formed as part of cover 204. In turn, cylinder member 268 leads into filter chamber 202.

The manner in which fluid and entrained particles flows through pump assembly 30 during operation of dishwasher 2 will now be described. In a manner known in the art, tub 5 will be initially, partially filled with water which can be further heated by activation of heating element 44. During a washing cycle, motor 165 is activated in order to concurrently rotate chopper blade 178 and impeller 220. In this manner, the washing fluid with entrained particles will be drawn into trough 129 between fins 200 of strainer 36. Given the distances between the respective fins 200 of strainer 36, any large food pieces, utensils or the like will be caught by strainer 36 in the bottom of tub 5 instead of entering pump assembly 30 where they may cause damage. The

combination of strainer fins 200 and rib or flow plate 198 establishes the flow and the size of entrained soil particles which can enter pump assembly 30. Therefore, this washing fluid, which will initially be substantially clean but which will certainly pick-up additional soil during
5 at least initial stages of a washing operation, will flow past strainer fins 200, down into trough 129, beneath flow plate 198, up an opposing portion of trough 129 to an intake chamber 269 defined between lower housing plate 145 and intermediate housing plate 189.

As the washing fluid is being drawn in by at least the operation of
10 impeller 220, the washing fluid will attempt to flow through apertured plate 182. At this point, the rotating chopper blade 178 will function to mince any entrained particles within the washing fluid, with the particles having to be chopped sufficiently in order to enable passage through apertured plate 182. Therefore, flowing through apertured plate 182 will
15 be a liquid having, at most, small soil particles entrained therein. When this fluid supply is directed between pump component 218 and impeller 220, the fluid is directed radially outwardly into a pumping chamber 270. The fluid is then forced to reverse direction and to flow through involute manifold 226.

20 Therefore, at involute manifold 226, the fluid is directed radially inwardly and then upwardly, with a portion of the fluid flowing through to and causing rotation of lower wash arm 47 and a substantial portion of the fluid being directed into conduit 51. The portion of fluid flowing into lower wash arm 47 will be sprayed into tub 5 through nozzles, such as
25 that indicated at 271, provided on lower wash arm 47 in order to direct the fluid upwardly against kitchenware supported upon a lower rack, as

well as a portion of the fluid downwardly as will be discussed more fully below.

With respect to the fluid flowing through conduit 51, a small percentage of this fluid will enter sampling port 267 so as to be directed through cylinder member 268 and into filter chamber 202. The remaining portion of the fluid in horizontal section 53 of conduit 51 will continue to flow through vertical section 54 and upper horizontal section 55 in order to reach upper wash arm 59 which is used to provide a downward flow of washing fluid onto the kitchenware. As indicated above, a portion of the fluid flowing through conduit 51 can also be diverted through a respective port 68, 69 through the use of wash fluid diverter 66.

The portion of the fluid that flows into filter chamber 202 will actually be forced to flow around filter chamber 202 which is open to collection chamber 212 and drain port 76. However, when drain pump 79 is not activated, this fluid and the entrained particles therein can only initially fill up collection chamber 212 and filter chamber 202. Once chambers 202 and 212 are filled, the fluid will be caused to flow out of pump housing 33 and back into tub 5 through the various enlarged openings 206 provided with fine mesh screen 207. Of course, given the presence of fine mesh screen 207, the fluid re-entering tub 5 from filter chamber 202 will be substantially cleansed of any soil having any substantial particulate size. Any soil particles which are larger than that which can flow through screen 207 will be forced to remain within filter chamber 202 and will actually find their way into collection chamber 212 due to the current flow created by incoming fluid into filter chamber 202 through sampling port 267 and gravity. In any event, this cleansed

washing fluid will be mixed with the remaining fluid in tub 5 and, in fact, re-mixed with the re-circulated fluid flowing out of at least lower wash arm 47 and upper wash arm 59.

With this arrangement, continued recirculation of washing fluid
5 will assure that all of the soil particles are finely chopped by blade 178 as all the washing fluid entering intake chamber 269 can only pass to pumping chamber 270 through chopper blade 178 and fixed apertured plate 182. Furthermore, by continuing to provide a flow into sampling port 267 and further finely filtering particles entrained in this fluid by
10 means of fine mesh screen 207, the percentage of soil in the recirculated washing fluid actually becomes quite small. Of course, soil will be accumulating within collection chamber 212, along with a certain percentage in filter chamber 202. Furthermore, since the fluid is attempting to exit pump assembly 30 through fine mesh screen 207, the
15 underside of fine mesh screen 207 itself will actually start to accumulate soil and can become clogged. For this purpose, lower wash arm 47 is provided with one or more lower nozzles, one of which is indicated at 273 in Figure 6, in order to direct a spray of washing fluid onto fine mesh screen 207. Therefore, this directed flow will tend to wash particles off
20 of fine mesh screen 207 and back into filter chamber 202 and, eventually, to collection chamber 212.

Regardless of this arrangement, fine mesh screen 207 can become significantly clogged so as to undesirably reduce the flow of cleansed washing fluid therethrough. Obviously, such a clogged arrangement
25 results in an increase in pressure within filter chamber 202. Granted, a substantial increase in pressure could cause washing fluid to flow into

drain hose 85 upon exceeding a drain loop head. However, this increased pressure forces washing fluid to flow from within filter chamber 202 into overflow tube 98, which is in direct fluid communication with filter chamber 202 as perhaps best shown in Figures 4 and 5. Therefore, washing fluid from filter chamber 202 is forced up overflow tube 98 towards overflow housing 104. At this time, coarse filter 106 will function to at least limit the return of soil back into tub 5 until fine mesh screen 207 is cleansed as discussed further below.

In accordance with the most preferred embodiment, complete drainage operations are performed on a preprogrammed, timed basis. However, additional drain or purging operations can also be performed. In accordance with the invention, an initial drainage sequence is established depending on the dishwashing operation set by the user. For instance, if the user selects a normal wash mode, a fill operation will be performed wherein a certain amount of water, which will vary with dishwasher models (generally in the order of 6.5-8 quarts), is introduced into tub 5. Thereafter, a main wash cycle will be entered. In accordance with the most preferred form of the invention, the main wash cycle is set at 34 minutes. The main wash cycle is then followed by a rinse cycle lasting 25 minutes. Thereafter, a 30 minute dry cycle is entered.

In the alternative, the user can select a dirty wash cycle which would result, for example, in an 8 minute pre-wash, followed by: a 28 minute main wash cycle, a pre-rinse of 10 minutes, a main or final rinse of 25 minutes, and a 30 minute drying period. With these configurations, the normal and dirty wash cycles would have 2 or 4 fill periods respectively. Correspondingly, there would be 2 or 4 drain operations

performed, each being approximately 2 minutes in duration. Therefore, the drainage operations are pre-programmed based on the particular washing cycle selected, i.e., provided at specific lapsed time periods during an overall dishwashing operation. However, it is possible for a user to select a normal wash mode when the amount of soil on the kitchenware justifies a dirty mode. To this end, dishwasher 2 includes a turbidity sensor 275 shown mounted beneath tub 5 while projecting into washing chamber 14, preferably in trough 129. Of course, the use of turbidity sensors to sense soil levels in dishwashers is widely known in the art. In accordance with the present invention, if a normal wash cycle is selected but turbidity sensor 275 indicates high soil levels, the pre-programmed dirty wash cycle operational sequence will be followed. Furthermore, turbidity sensor 275 incorporates a thermistor (not separately labeled) which is used in cycling of heater element 44. At this point, it should be noted that the location of turbidity sensor 275 within trough 129 is considered to be an advantageous feature as turbidity sensor 275 is more sensitive to turbulences developed by existing soil. Trough 129 actually functions as an air/water separator for pump assembly 30 such that the location of turbidity sensor 275 is also considered to enhance the accuracy of soil level signals.

In any case, during full or partial drainage operations, soil will be removed from at least collection chamber 212 when a combination of soil and washing fluid will be directed, through the operation of drain pump 79, into drain hose 85. During this time, it is preferred to continue the operation of pump assembly 30 in order that nozzles 273 can continue to enhance the cleaning of fine mesh screen 207. In addition, following the last drain operation in a given dishwashing cycle, a spritzing step is

preferably performed wherein a small amount of water is introduced to fill up trough 129 in order to assure that turbidity sensor 275 is covered so that a film will not develop thereon.

Washing fluid will continue to be pumped into drain hose 85 while fine mesh screen 207 is being purged of food soil, at which time the washing fluid in overflow tube 98 will drop back down to a normal level. Given the inclusion of filter 106 in overflow housing 104, only filtered washing fluid can enter tub 5 through overflow tube 98. In the most preferred embodiment, filter 106 actually incorporates a coarse mesh screen versus the fine mesh screen 207. Again, it should be realized that fine mesh screen 207 can become overwhelmed with food soil, particularly during pre-washes. However, coarse filter 106 performs a similar filtering function when the washing fluid with entrained soil is forced up overflow tube 98. When a washing or rinsing operation is being performed by dishwasher 2, it is preferred that a certain spray percentage be directed at filter 106, such as through the angling of a number of nozzles on upper wash arm 59 or on an intermediate, rack supported wash arm (not shown). Therefore, any soil that collects in filter 106 is washed back down overflow tube 98. When pump 30 remains activated during a drain operation, this flow of soil to drain is advantageously enhanced. During other cycles, the washing fluid sprayed on filter 106 will eventually cause collected soil to fall back to filter chamber 202 through overflow tube 98 due to gravity. There the soil would be separated from the washing fluid by fine mesh filter 207.

During drain operations, certainly soil retained in collection chamber 212, along with some of washing fluid within pump assembly

30, will be expelled. However, not all the drainage must flow through intake and pumping chambers 267 and 270 in accordance with the invention. That is, it is desirable to have some direct fluid communication between tub 5 and drain pump 79. This communication
5 is performed through the incorporation of a flapper valve 276 which is arranged in collection chamber 212 as shown in Figures 4-6 and 8. In accordance with the most preferred embodiment, flapper valve 276 includes an upper rim portion 277 and a plurality of downwardly directed flaps or legs 278. Although three legs 278 are shown, other
10 configurations, such as two or fours legs could be employed, with each of legs 278 constituting a wall section of collection chamber 212, while being arranged in trough 129. With this arrangement, when drain pump 79 is activated, the suction created in collection chamber 212 will deflect legs 278 closer together thereby permitting washing fluid from within tub
15 5 to directly enter collection chamber 212 and, subsequently, drain hose 85.

More specifically, the inclusion of flapper valve 276 provides a preferential drain for collection chamber 212 and filter chamber 202 before the sump defined by tub 5. That is, when a drain operation is
20 performed, the initial flow of washing fluid and soil from filter and collection chambers 202 and 212 will prevent legs 278 from deflecting inward, i.e., the flow past legs 278 tends to keep legs 278 closed against sides of collection chamber 212. Once this soil entrained fluid is drained, legs 278 will deflect inward to allow further draining of the washing fluid
25 from tub 5. Therefore, when legs 278 deflect inward, slots are created to allow flow to drain port 76. During normal washing and rinsing operations, flapper valve 276 also advantageously prevents collected soil

from returning to tub 5 about legs 278 when fine mesh screen 207 becomes clogged as an increase in pressure within filter chamber 202 will actually result in an outward biasing of legs 278. To this end, flapper valve 276 can substantially enhance the effectiveness of potential, partial
5 purging operations which really only require draining to occur until the point when legs 278 will deflect inward.

Figures 9-11 will now be referenced to describe the preferred construction and function of filter guard 39. Although filter guard 39 is illustrated in each of Figures 1-3, this structure has been removed from
10 Figures 4-7 to clearly depict other structure associated with pump assembly 30. In any event, as shown, filter guard 39 is mounted upon main housing 33 below lower wash arm 47. Filter guard 39 includes an outer wall 279 which slopes from an inner radial portion towards an outer radial portion. As depicted, filter guard 39 actually extends substantially
15 over strainer fins 200 but, more importantly, extends entirely over fine mesh screen 207. In essence, without the presence of filter guard 39, utensils and other objects could inadvertently fall within tub 5 and damage fine mesh screen 207. Therefore, filter guard 39 is provided to shield fine mesh screen 207, while outer wall 279 is angled to
20 accommodate run-off of any washing fluid.

As clearly shown in these figures, the outer wall 279 of filter guard 39 is provided with various wash-out regions 280, with these wash-out regions also having associated therewith mounting holes 281 in bosses 282 for securing filter guard 39 to main housing 33. Further, along an
25 underside of filter guard 39 at wash-out regions 280 are a plurality of ribs 283. In addition, between adjacent bosses 282 are provided spacer ribs

285. Indentations or recesses 289 and 290 are provided around the periphery of filter guard 39, with recesses 289 and 290 being essentially located at mounting locations for heating element 44 as clearly illustrated in Figure 1.

5 In a manner commensurate with outer wall 279, filter guard 39 has an underside 292 which curves in order to enhance the directing of wash arm spray for the backwashing of fine mesh screen 207. That is, as previously indicated, lower wash arm 47 includes at least one set of nozzles 273 for use in directing a spray to backwash and cleanse fine
10 mesh screen 207. Filter guard 39 is spaced sufficiently from pump housing cap 235 and nozzles 273 are suitably angled to accommodate this spray upon fine mesh screen 207. However, the curvature of underside 292 further enhances this backwashing function. Wash-out regions 280 are provided for flushing out trapped food particles in connection with the
15 overall filter guard 39.

 Although overflow tube 98 is shown to be integrated into conduit 51, it is possible to provide a separate overflow tube 98a (see Figure 12). Tube 98a is shown to extend adjacent to conduit 51, but actually could be directed to another portion within tub 5 distinct from conduit 51. That is,
20 where conduit 51 extends generally along a central portion of rear wall 11, it is possible to direct overflow tube 98a to a corner or side of tub 5. Such an arrangement could enhance the accessibility to filter 106 if changing thereof is warranted.

 Obviously, dishwasher 2 needs to perform various operations in
25 connection with a washing operation wherein heater 44, drain pump 79

and pump motor 165 are controlled. Figure 13 schematically illustrates the control system used to regulate dishwasher 2 in the manner set forth above through a controller or CPU 295 based on operator inputs made at a control panel as generically represented at 296 and signals from
5 turbidity sensor 275, which also includes the thermistor as discussed above, provided in tub 5 outside of pump assembly 30. Regardless, it should be readily apparent that the disclosed pump and filtration arrangement provides multiple stage filtrations through the use of strainer 36, sampling port 267 and fine mesh screen 207. In addition, employing
10 the filter guard advantageously protects the fine mesh filter while enhancing the backwashing thereof. To this end, it is important to note that the filter guard is fixed, as opposed to rotating with the lower wash arm, thereby reducing the weight of the rotatable wash arm assembly and simplifying the balancing.

15 Of particular interest in connection with performing a washing operation in dishwasher 2 according to the present invention is employing a wash and rinse system that functions to dislodge food and soil particles that may adhere to portions of walls 8-12 of washing chamber 14. In accordance with a preferred embodiment of the present invention, at the
20 start of either a wash or rinse cycle, washing chamber 14 is initially filled with washing fluid to a first level by opening a water valve 310 through CPU 295. More specifically, washing chamber 14 is filled with washing fluid to a level approximately even with bottom portion 21 of door 20. Once washing chamber 14 is filled to the first level, the wash or rinse
25 cycle is initiated. Upon activation of the particular cycle, pump assembly 30 draws the washing fluid into main housing 33 causing the washing fluid remaining in washing chamber 14 to fall to a second, lower level.

Pump assembly 30 then directs the washing fluid to at least wash arm 47. Actually, pump assembly 30 preferably directs the washing fluid to an overall washing system including wash arm 47, conduit 51 and upper wash arm 59. Upon being supplied with washing fluid, wash arm 47 will
5 begin to rotate, spraying jets of washing fluid onto the kitchenware such that food and soil particles are dislodged in order to be directed into pump assembly 30 for filtering and drainage. However, some of the particles will impinge upon and also undesirably adhere to walls 8-12 of washing chamber 14. In order to dislodge the food and soil particles that adhere to
10 walls 8-12 in accordance with the present invention, washing chamber 14 is once again filled to the first level. In this manner, food and soil particles that may become trapped below lower lip portion 25 of liner 24 or other regions of washing chamber 14 that are not directly exposed to the jets of washing fluid can be dislodged and subsequently directed to
15 pump assembly 30.

In accordance with the most preferred form of the present invention, washing chamber 14 is refilled to the first level by deactivating motor 165 of pump assembly 30. In this manner, washing fluid suspended in the overall wash system falls, under the force of gravity,
20 back into washing chamber 14, thereby causing the washing fluid to return to the first level. After a predetermined pause period which advantageously allows the washing fluid to soak into and dislodge the food and soil particles, pump assembly 30 is once again reactivated, drawing the washing fluid back into the washing system. Preferably, the
25 pause periods are repeated several times throughout wash and rinse cycles of an overall washing operation. More preferably, the pause periods are

carried out both during a main wash cycle and the main or final rinse cycle.

After each pause period, pump assembly 30 once again directs washing fluid throughout the wash system. In still further accordance with the most preferred form of the present invention, pump assembly 30 gradually increases a pressure of the washing fluid being delivered to wash arm 47 in order to create a random spray pattern within washing chamber 14. Actually, by gradually increasing the pressure of washing fluid being delivered to wash arm 47, a trajectory of the jet of washing fluid emanating from wash arm 47 is varied proportionally. In this manner, wash arm 47 can deliver jets of washing fluid to areas or regions of washing chamber 14 typically not directly hit by the jets of washing fluid under normal operating conditions. To this end, food and soil particles adhering to walls 8-12 in regions above the first level of washing fluid can be loosened and directed to pump assembly 30 for a subsequent filtration and drainage operation. Particularly, corner portions of washing chamber 14 and the lower frontal lip (not separately labeled) of tub 5 that is at least partially shielded by a lower section of door 20 from being impacted by jets of washing fluid during a washing sequence will be impacted by the jets of washing fluid. In this manner, the wash and rinse system of the present invention will dislodge food and soil particles that would otherwise accumulate on walls 8-12 of washing chamber 14 and ultimately either degrade the overall efficiency of the various washing operations or permanently stain internal surfaces of walls 8-12.

Although described with reference to a preferred embodiment of the invention, it should be readily understood that various changes and/or

modifications can be made to the invention without departing from the spirit thereof. In any event, it should be understood that the invention is only intended to be limited by the scope of the following claims.